

# METAL WIDTH / GAUGE

## CALCIUM SILICATE 360° PIPE SUPPORTS WITH GALVANIZED SHIELD

Copper Tube O.D. in Inches	Iron Pipe in Inches	Insulation Thickness in Inches					
		1/2"	1"	1-1/2"	2"	2-1/2"	3"
5/8"			4" / 24 ga	4" / 24 ga	4" / 24 ga	4" / 20 ga	6" / 20 ga
7/8"	1/2"		4" / 24 ga	4" / 24 ga	4" / 24 ga	4" / 20 ga	6" / 20 ga
1-1/8"	3/4"		4" / 24 ga	4" / 24 ga	4" / 24 ga	4" / 20 ga	6" / 20 ga
1-3/8"	1"		4" / 24 ga	4" / 24 ga	4" / 24 ga	4" / 20 ga	6" / 20 ga
1-5/8"	1-1/4"		4" / 24 ga	4" / 24 ga	4" / 24 ga	4" / 20 ga	6" / 20 ga
	1-1/2"		4" / 24 ga	4" / 24 ga	4" / 24 ga	4" / 20 ga	6" / 20 ga
2-1/8"			4" / 24 ga	4" / 24 ga	4" / 24 ga	4" / 20 ga	6" / 20 ga
	2"		6" / 20 ga	6" / 20 ga	6" / 20 ga	6" / 20 ga	6" / 20 ga
2-5/8"			6" / 20 ga	6" / 20 ga	6" / 20 ga	6" / 20 ga	6" / 20 ga
	2-1/2"		6" / 20 ga	6" / 20 ga	6" / 20 ga	6" / 20 ga	9" / 20 ga
3-1/8"			6" / 20 ga	6" / 20 ga	6" / 20 ga	6" / 20 ga	9" / 20 ga
	3"		6" / 20 ga	6" / 20 ga	6" / 20 ga	6" / 20 ga	9" / 20 ga
3-5/8"			6" / 20 ga	6" / 20 ga	6" / 20 ga	6" / 20 ga	9" / 20 ga
	3-1/2"		6" / 20 ga	6" / 20 ga	6" / 20 ga	6" / 20 ga	9" / 20 ga
4-1/8"			6" / 20 ga	6" / 20 ga	6" / 20 ga	6" / 20 ga	9" / 20 ga
	4"		6" / 20 ga	6" / 20 ga	6" / 20 ga	6" / 20 ga	9" / 20 ga
	4-1/2"		6" / 20 ga	6" / 20 ga	6" / 20 ga	6" / 20 ga	9" / 20 ga
	5"		6" / 20 ga	6" / 20 ga	6" / 20 ga	6" / 20 ga	9" / 20 ga
	6"		6" / 20 ga	6" / 20 ga	6" / 20 ga	6" / 18 ga	9" / 18 ga
	7"		9" / 16 ga	9" / 16 ga	9" / 16 ga	9" / 16 ga	9" / 16 ga
	8"		9" / 16 ga	9" / 16 ga	9" / 16 ga	9" / 16 ga	9" / 16 ga
	9"		9" / 16 ga	9" / 16 ga	9" / 16 ga	9" / 16 ga	9" / 16 ga
	10"		9" / 16 ga	9" / 16 ga	9" / 16 ga	9" / 16 ga	9" / 16 ga
	11"		12" / 16 ga	12" / 16 ga	12" / 16 ga	12" / 16 ga	12" / 16 ga
	12"		12" / 16 ga	12" / 16 ga	12" / 16 ga	12" / 16 ga	12" / 16 ga

SUBJECT TO CHANGE WITHOUT NOTICE.

REV. 1/30/09